

Caliber 3201

## 516.53.39.50.02.001

- () Co-Axial escapement
- 🗊 Manual
- Tachymeter
- Pulsometer
- Sapphire crystal
- Anti-reflective treatment on both sides
- 🕦 Gold 750‰ (18K)
- **Limited Edition**
- Water-Resistant to a relative pressure of 3 bar (30 metres/100 feet)



## WATCH FUNCTIONS

The crown has 2 positions:

**1. Normal position (wearing position):** when the crown is positioned against the case, the crown ensures that the watch is water-resistant.


Winding: turn the crown forwards until it stops (DO NOT OVERWIND).

Note: do not wind the watch more often than is necessary. For a watch that is worn all the time, a single winding each day will ensure that it functions correctly.

**2. Time setting:** hours – minutes – seconds. Pull the crown out to position 2. Turn the crown forwards or backwards. Synchronise the seconds by pushing the crown back to position 1 to coincide with a given time signal.

Timing to 1/8 of a second for up to 12 hours.

Note: resetting/zeroing of the sub dials must only be carried out after the chronograph has stopped. Never push the chronograph's two pushers (A and B) simultaneously.



## TACHYMETRIC SCALES

The desired information is read between the central seconds hand of the chronograph and the corresponding scale, over a maximum duration of 60 seconds.

Example: calculating the speed of a car.

Record the time the car takes to cover a distance of 1 kilometre. Read off the tachymetric scale the speed indicated by the central seconds hand. In this case, the car is travelling at 120 km/h.

## PULSOMETRIC SCALES

The desired information is read between the central seconds hand of the chronograph and the corresponding scale, over a maximum duration of 60 seconds.

Example: calculating the number of heart-beats per minute.

Start the chronograph, count the heartbeats and stop it at the beat corresponding to the scale graduations of your chronograph (here to the 30th beat). Read the number of beats per minute off the pulsimetric scale: here, 60 beats/minute.



